

Product Data Sheet

672-(1)-04/14



Makers of Fine Paint Since 1962

ISSUED: 24 April 2014

Page 1 of 2

672 Tung Oil Sealer

USE




THINNER/CLEAN



Mineral
Turpentine

APPLICATION



RE-COAT



8 - 12 Hrs

HAZARD



672 Tung Oil Sealer is a single pack, traditional, tung oil resin based timber sealer, for use on interior timber. It is particularly suitable for use on timber board floors where excessive shrinkage or expansion is likely to occur.

USES: For use on interior timber surfaces such as floors, doors, skirtings, windows, furniture and timber paneling.

COLOUR: Clear light honey colour. 672 Tung Oil Sealer will enhance the natural colour of the timber and can be coloured by intermixing with a compatible stain and can also be applied over most oil or spirit stains.

SURFACE PREPARATION: Surfaces must be thoroughly dry, and free of all dirt, grease and wax, prior to application. Sand timber to a smooth surface and ensure that all sanding dust is removed.

NEW INTERIOR TIMBER: Apply 2 to 3 coats directly to timber. Lightly sand between every coat. Use grade 280-320 paper.

PREVIOUSLY COATED SURFACES: Remove all existing two-pack, moisture cured urethane coatings or unknown coatings prior to applying 672 Tung Oil Sealer.

PREVIOUSLY COATED WITH TUNG-OIL SEALER: Surfaces must be thoroughly dry. All waxes, polish, grease, and dirt must be removed prior to application. Lightly sand surface using grade 280-320 paper, to provide a key, and ensure that all sanding dust is removed.

MAINTENANCE: For high traffic areas 645 Mop Top a re-coatable liquid, non-wax polish may be applied over 672 Tung Oil Sealer to add further durability and ease of maintenance. NOTE: Allow a curing period of at least 4 weeks before applying 645 Mop Top.

APPLICATION: Brush, Quality short nap roller or lambskin applicator.

MIXING: Stir well with a flat paddle or "potato masher" type stirrer before and during use. Do NOT power mix or shake can as excessive bubbles may be introduced into the product.

COVERAGE: Hardwoods approx. 10m² - 12m² per Litre. Softwoods approx. 8m² - 10m² per Litre. Coverage depends on porosity of timber.

DRYING TIME: Dust dry 1 hour. Touch dry approx. 4 hours at 25°C. Lower temperatures will increase times. Do not apply if ambient or surface temperature is below 10°C or above 35°C.

RE-COAT TIME: 8 to 12 hours at 25°C. Lower temperatures will increase times.

NOTE: This product must not be applied when the air or surface temperature are below 10°C or above 30°C

THINNERS: Thinning is not recommended.

CLEAN UP: Clean equipment with Mineral Turpentine. For stronger cleaning use 679 Brush Kleen. Do not clean hands with solvents or 679 Brush Kleen, use suitable hand cleaner.

STRIPPING: If for any reason it is necessary to strip 672 Tung Oil Sealer, 675 Paint Stripper is recommended.

Packaging: 1 litre, 4 litre 10 litre and 20 litre cans.

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





672 Tung Oil Sealer

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes