

Product Data Sheet

684-(2)-05/14




Makers of Fine Paint Since 1962

ISSUED: 05 May 2014

Page 1 of 2

684 Super Wash

USE




THINNER/CLEAN



Water


APPLICATION



RE-COAT



HAZARD



684 Super Wash is a water based, biodegradable, industrial strength, multipurpose cleaning detergent suitable for the preparation of swimming pool surfaces and floors prior to painting. 684 Super Wash is non-flammable and has virtually no odour making it suitable for use in confined areas.

USES: Forminex 684 Super Wash is also suitable for general cleaning of industrial equipment, transport fleets, vehicles, boats and routine janitorial cleaning.

684 Super Wash is Biodegradable to AS 1792 and safe for use in food contact areas.

684 Super Wash was formerly sold as both Forminex Pool Wash and Forminex Floor Wash.

POOL AND FLOOR CLEANING: Mix 500ml Forminex 684 Super Wash into 20 litres of fresh water. Apply solution to smaller areas at a time, scrub into surface & thoroughly rinse off with fresh water. Do not allow cleaning solution to dry on surface.

FOR STRONGER CLEANING: Mix Forminex 684 Super Wash 1:1 with water to clean areas with heavy deposits of grease or oil. Scrub into surface and allow to sit for 5 minutes. Thoroughly rinse off with fresh water. Do not allow cleaning solution to dry on surface.

Note: After cleaning the pool or floor **MUST** be left to dry for 2 – 3 days to allow it to thoroughly dry prior to painting.

OTHER INFORMATION: Do not allow 684 Super Wash or rinse water to enter storm water drains or gutters as doing so may contravene local regulations. Check with local Authorities.

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





684 Super Wash

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes