

Product Data Sheet

809-(7)-04/14



Makers of Fine Paint Since 1962

ISSUED: 28 April 2014

Page 1 of 2

809 Pink Wood Primer

USE



THINNER/CLEAN



Turpentine

APPLICATION



RE-COAT



24 Hrs

HAZARD



A top quality lead free, traditional, oil based primer suitable for the use on most interior and exterior wood surfaces. 809 Pink Wood Primer has the excellent ability to penetrate and seal on new and old unpainted timber.

USES: A primer for all bare interior or exterior timber surfaces. 809 Pink Wood Primer's particular function is to provide the protection for timber and a good key for the succeeding coats of either undercoat or finishing paint. 809 Pink Wood Primer can also be useful as a primer for modern "no-primer required" exterior timber finishes such as 806 Solacryl particularly on badly weathered timber.

SURFACE PREPARATION: Surface to be primed should be clean, dry, free from oil and grease.

New Timber: Sand well with before applying.

Previously Painted Timber: Remove old flaking paint with a scraper, wire brush or heat gun. Fill holes and cracks with a suitable filler and allow to fully dry. Sand the surface thoroughly with 120-180 grit sandpaper and wipe down or vacuum to remove dust. Ensure surface is clean. Thoroughly sand glossy surfaces with 180-220 grit sandpaper prior to painting.

Bare exterior timber should be primed within 7 days or the surface will have deteriorated and adhesion and subsequent performance of the paint system could be compromised. If this occurs the surface should be sanded before painting.

APPLICATION: Stir thoroughly until product is uniform. For maximum penetration, brush application is recommended, It is recommended to apply 2 coats to end grain to ensure no moisture penetrates the timber. However, 809 Wood Primer may also be applied by conventional spray equipment.

THINNING: For brush application it is ready to use. However, if required, Mineral Turpentine may be used sparingly. For spray application thin with F-200 Reducer.

CLEAN UP: Clean brushes and equipment with Mineral Turpentine.

DRYING: Re-coating is possible after 24 hours drying at 25°C.

COLOUR: Pink.

FINISH: Lo Sheen.

COVERAGE: Theoretical coverage is 12-14 m²/Litre at 50 micrometres dry film thickness.

PACK SIZES: 1 Litre, 4 Litre.

VEHICLE TYPE: Blend of pure oils and alkyd.

PIGMENT TYPE: Titanium Dioxide, Zinc Oxide, inert extenders.

FILM PROPERTIES:

Solvent Resistance	Good.	Chemical Resistance	Fair.
Abrasion Resistance	Fair.	Impact Resistance	Good.
Heat Resistance	Good up to 100°C (dry).	Flexibility	Good.

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.



Product Data Sheet

809-(7)-04/14



Makers of Fine Paint Since 1962

ISSUED: 28 April 2014

Page 2 of 2

809 Pink Wood Primer

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.

